



## Surface Mounted Speaker and Microphone

STS-S60-G / STS-S60-B  
STS-M54-G / STS-M54-B

Our customer side, free-standing speaker and omnidirectional microphone modules.

### Physical Data

Dimensions	Height – 75mm (2.95") Width – 60mm (2.36") Depth – 110mm (4.33")
Weight	550g (1.21lbs)
Construction	Mild Steel
Finish	Grey Powder Coated Leatherette
	Black Textured Powder Coated

### Technical Data

Speaker	RMS	5W
	Impedance	4Ω
	Output	SPL 1W @ 1M 85dB
	Frequency Response	150Hz - 10300Hz
Microphone	Directional Response	Omnidirectional
	Frequency Response	100Hz - 5000Hz
	Sensitivity	-42.5 ± 2.0dB @ 1KHz (0dB=1V/pa)
	Impedance	2K Ohms =/- @ 1KHz

### Applications

For use where one to one communication takes place at a counter or booth with a security screen:

- Banks
- Post Offices
- Ticket Kiosks
- Information Centres
- Airports

Talk to us now:  
+44 (0) 1732 223900 (UK & ROW)  
+1 616 392 3400 (US & Canada)  
[www.contacta.co.uk](http://www.contacta.co.uk)

